

NORMA 43 *flexible homogeneous floor covering with PUR Protection*



0001



0003



0031



0002



0040



0042



0030



0081



0080



0041



0052



0025



0061



0060



0064



0062



0071



0072



0015



0011



0013



0012



0010



0070

NORMA 43 *flexible homogeneous floor covering with PUR Protection*



a pressed floor covering with static dissipative properties. Available in sheets. Has a non dimensional print. Protected with polyurethane PUR. Resistant to microorganisms (bacteria and fungus). Suitable for use in high-traffic public buildings, rooms where people are present permanently, intensively used light-industry facilities and areas where antistatic protection is required.

Specification

Warranty		15 years
EC Certificate of Conformity	PN-EN 14041	1488-CPD-0017/W
Usability Class	PN-EN 649 + 685	34 / 43
Reaction to Fire	PN-EN 13501-1	B _μ - s1
Hygiene Attest		Pass
Electrical Properties	PN-EN 14041	Astatic and dissipating
Electrical Resistance	PN-EN 1081	≤ 10 ⁹ Ω
Electrostatic Voltage	PN-EN 1815	≤ 2 kV
Slip Resistance	DIN 51130 PN-EN 14041	R11 Class DS
Dynamic Coefficient of friction	PN-EN 13893	0.37 / 0.34
Wear Resistance	PN-EN 660-1 PN-EN 660-2	Group T
Residual Indentation	PN-EN 433	0.04 mm
Dimensional Stability after heat exposure	PN-EN 434	≤ 0.4 %
Curling after heat exposure	PN-EN 434	≤ 8 mm
Light Resistance	PN-ISO 105-B02	> 7
Flexibility	PN-EN 435	Good
Chemical Resistance	PN-EN 423	Good
Resistance to microorganism	PN-EN ISO 846	Yes
Thickness / Width / Length		2.0 mm / 2 m / 20 m
Weight		2.6 kg / m ²